

# 6X6 - 12 FT STAND ECONOMY BLIND




SCAN FOR  
INSTRUCTIONS

800-763-7320  
RANCHKINGBLINDS.COM

## KIT BAG CONTENTS

- 24 - 1 1/4" x 3/8" BOLTS
- 2 - 2 1/2" x 3/8" BOLTS
- 26 - 3/8" LOCK NUTS
- 4 - 3/8" WASHERS
- 20 - 3/4" SELF-TAPPING SCREWS
- 8 - 1 1/4" SELF-TAPPING SCREWS
- 4 - LADDER END CAPS

## 6X6 - 12 FT STAND ECONOMY BLIND



104" LOWER BRACES - FOUR PIECES

118 1/2" CROSS BRACES - FOUR PIECES

144" NUMBERED BLIND LEGS

40" PLATFORM BRACES - TWO PIECES

○ LEGS ARE MARKED AND INSTALLED WITH THE LEG NUMBER ON THE LEG AND BASE

- Raise blind, remove shipping legs and slide in tower legs, make sure legs are in all the way, attach with 3/8 bolts
- Lower to 2" off the ground
- Install all braces, leave 3/8 bolts and lock nuts loose at this time
- Set blind on a level surface, pull out all legs to settle the blind into it's final position
- Tighten all bolts
- Raise platform and install five 3/8" bolts, level platform by setting equal gap between vertical railing and the blind.
- Install 40" braces from Leg One and Leg Two to platform using 3/8 bolts and lock nuts
- Attached ladder to platform using 2 1/2" x 3/8 bolts. Be sure to install bolt threads towards the outside, then keeps bolts from creating a tripping hazard.
- Install left and right ladder hand rails with 3/4" self-tapping screws
- Push in plastic ladder end caps on each end of the ladder rails