

LITTLE BUCK 4FT ECONOMY BLIND




SCAN FOR
INSTRUCTIONS

800-763-7320
RANCHKINGBLINDS.COM

KIT BAG CONTENTS

- 20 - 1" x 3/8" BOLTS
- 2 - 2 1/2" x 3/8" BOLTS
- 22 - 3/8" LOCK NUTS
- 4 - 3/8" WASHERS
- 20 - 3/4" SELF-TAPPING SCREWS
- 8 - 1 1/4" SELF-TAPPING SCREWS
- 4 - LADDER END CAPS

LITTLE BUCK 4FT ECONOMY BLIND



50 1/2" LOWER BRACES - TWO PIECES

56" CROSS BRACES - FOUR PIECES

60" NUMBERED BLIND LEGS

○ LEGS ARE MARKED AND INSTALLED WITH THE LEG NUMBER ON THE LEG AND BASE

- Raise blind and remove shipping legs. Attach legs using 3/8 bolts and lock nuts leave loose at this time
- Lower to 2" off the ground
- Install all braces, leave 3/8 bolts and lock nuts loose at this time
- Set blind on a level surface, pull out all legs to settle the blind into it's final position
- Tighten all bolts
- Attach ladder to base using 2 1/2" x 3/8 bolts. Be sure to install bolt threads towards the outside, then keeps bolts from creating a tripping hazard.
- Install right ladder hand rails with 3/4" self-tapping screws
- Push in plastic ladder end caps on each end of the ladder rails